

## POWERPULSE & ACTIPULSE 288 Low-Flow SERIES

TOOL SIZE		2 7/8 inch (73 mm)	
CONFIGURATION	288	288 SS	
ASSEMBLY #	IA10080	IA10147	
LENGTH	82 inch (2.08 m)	103 inch (2.61 m)	
AVAILABLE CONFIGURATIONS	PowerPulse® ActiPulse®		
RECOMMENDED FLOW RANGE *	1 BBL/min to 3 BBL/min 42 GPM to 126 GPM (0.15 to 0.50 m³/min)		
FREQUENCY RANGE	5 to 14 Hz		
AVERAGE OPERATING FLOW PRESSURE DROP	400 to 700 psi (2750 to 5000 kPa)		
MAX TEMPERATURE *	Standard: 285 °F (140 °C) Hi-Temp: 375 °F (190 °C)		
STANDARD END CONNECTIONS	2-3/8 P.A.C.-DSI		
TORSIONAL STRENGTH	5,520 Ft-lbs. (7,480 Nm)		
BODY CONNECTIONS TORSIONAL STRENGTH	5,520 Ft-lbs. (7,480 Nm)		
TENSILE YIELD	140,000 Lbs. (62,300 daN)		
RECOMMENDED MAXIMUM PULL	105,000 Lbs. (62,300 daN)		
ActiPulse® DROP BALL SIZE	0.875 inch (22 mm)		
* For operating parameters outside listed specifications, consult with Impulse Representative			

**SS** - INDUCES AXIAL  
MOVEMENT INTO THE  
WELLBORE



**BALL-ACTUATED  
FRICTION  
REDUCTION**



### IMPULSE DOWNHOLE TOOLS

No part of this publication may be reproduced, distributed, or transmitted in any form or by any means without the written consent of Impulse Downhole Tools. All end thread connections may be either certified or industry standard compatible. US and Canadian Patents Granted and Patents Pending Worldwide.

<https://www.impulsedownhole.com/patents>